

## SAFETY DATA SHEET

TFR AND POLISH

Page 1

Issued: 16/08/2010

Revision No: 2

### 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

**Product name:** TFR AND POLISH

**Product code:** 316

**Use of substance / preparation:** 316 : A specialist alkali detergent for removing traffic film from vehicles and leaving a water repellent finish.

**Company name:** Clover Chemicals Ltd  
Clover House  
Macclesfield Road  
Whaley Bridge, High Peak  
Derbyshire  
SK23 7DQ  
UK  
Tel: +44 (0) 1663 733114  
Fax: +44 (0) 1663 733115  
Email: technical@cloverchemicals.com

### 2. HAZARDS IDENTIFICATION

**Main hazards:** Causes burns.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

- Hazardous ingredients:** AMPHOTERIC SURFACTANT 2-5%  
EINECS: )  
[Xi] R36
- C 12/15 A, 3-12 EO MULTIBRANCHED (DID 27) 2-5%  
EINECS: POLYMER CAS: 24938-91-8  
[Xn] R22; [Xi] R41
  - /-ALKYLDIMETHYLBENZYLAMMONIUM CHLORIDE 2-5%  
EINECS: 269-919-4  
[Xn] R22; [C] R34
  - SODIUM HYDROXIDE 2-5%  
EINECS: 215-185-5 CAS: 1310-73-2  
[C] R35
  - C9/11 A, >3-6 EO PREDOMINANTLY LINEAR (DID 21) 1-2%  
EINECS: POLYMER CAS: 160875-66-1  
[Xi] R41

### 4. FIRST AID MEASURES (SYMPTOMS)

**Skin contact:** Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

**Eye contact:** Corneal burns may occur. May cause permanent damage.

[cont...]

**SAFETY DATA SHEET**

TFR AND POLISH

**Ingestion:** Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.

**Inhalation:** There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

**4. FIRST AID MEASURES (ACTION)**

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Transfer to hospital if there are burns or symptoms of poisoning.

**Eye contact:** Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

**Ingestion:** Wash out mouth with water. Do not induce vomiting. Give 1 cup of water to drink every 10 minutes. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. Transfer to hospital as soon as possible.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious and breathing is OK, place in the recovery position. If conscious, ensure the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Transfer to hospital as soon as possible.

**5. FIRE-FIGHTING MEASURES**

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

**Exposure hazards:** Corrosive. In combustion emits toxic fumes.

**Protection of fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

**6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions:** Notify the police and fire brigade immediately. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

**Clean-up procedures:** Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Transfer to a suitable container.

**7. HANDLING AND STORAGE**

**Handling requirements:** Avoid direct contact with the substance. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

**Storage conditions:** Store in cool, well ventilated area. Keep container tightly closed.

**Suitable packaging:** Stainless steel. Teflon. Polyethylene. Do not use aluminium containers.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

- Hazardous ingredients:** SODIUM HYDROXIDE  
WEL (15 min STEL): 2 mg/m<sup>3</sup>
- Hand protection:** Impermeable gloves. Gloves (alkali-resistant).
- Eye protection:** Tightly fitting safety goggles. Ensure eye bath is to hand.
- Skin protection:** Impermeable protective clothing.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

- State:** Liquid
- Colour:** Off-white
- Odour:** Characteristic odour
- Evaporation rate:** Moderate
- Oxidising:** Non-oxidising (by EC criteria)
- Solubility in water:** Soluble
- Viscosity:** Non-viscous
- Boiling point/range°C:** 100
- Melting point/range°C:** 0
- Relative density:** 1.05 - 1.15
- pH:** 13 - 13.5
- VOC g/l:** 0

**10. STABILITY AND REACTIVITY**

- Stability:** Stable under normal conditions.
- Conditions to avoid:** Heat.
- Materials to avoid:** Strong oxidising agents. Strong acids.
- Haz. decomp. products:** In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

**11. TOXICOLOGICAL INFORMATION**

- Hazardous ingredients:** C 12/15 A, 3-12 EO MULTIBRANCHED (DID 27)  
ORL RAT LD50 1.5 g/kg
- SODIUM HYDROXIDE  
IPR MUS LD50 40 mg/kg  
ORL RBT LDLO 500 mg/kg
  - C9/11 A, >3-6 EO PREDOMINANTLY LINEAR (DID 21)  
ORL RAT LD50 >2000 mg/kg
- Routes of exposure:** Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

**12. ECOLOGICAL INFORMATION**

- Hazardous ingredients:** C 12/15 A, 3-12 EO MULTIBRANCHED (DID 27)  
FISH 96H LC50 >1 mg/l

**SAFETY DATA SHEET**

TFR AND POLISH

- C9/11 A, >3-6 EO PREDOMINANTLY LINEAR (DID 21)

ALGAE Scenedesmus 48H EC50 10 - 100 mg/l

**Mobility:** Readily absorbed into soil.**Persistence and degradability:** Biodegradable. The surfactants contained in this preparation comply with the biodegradability criteria as laid down in regulation (EC) No.648/2004 on detergents.**Bioaccumulative potential:** No bioaccumulation potential.**Other adverse effects:** Negligible ecotoxicity.**13. DISPOSAL CONSIDERATIONS****Disposal of packaging:** Dispose of as normal industrial waste.**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.**14. TRANSPORT INFORMATION****ADR / RID**

<b>UN no:</b>	1760	<b>ADR Class:</b>	8
<b>Packing group:</b>	III	<b>Classification code:</b>	C9
<b>Shipping name:</b>	CORROSIVE LIQUID, N.O.S. (( SODIUM HYDROXIDE ))		
<b>Labelling:</b>	8	<b>Hazard ID no:</b>	80

**IMDG / IMO**

<b>UN no:</b>	1760	<b>Class:</b>	8
<b>Packing group:</b>	III	<b>EmS:</b>	F-A,S-B
<b>Marine pollutant:</b>	.		
<b>Labelling:</b>	8		

**IATA / ICAO**

<b>UN no:</b>	1760	<b>Class:</b>	8
<b>Packing group:</b>	III		
<b>Packing instructions:</b>	818(P&CA); 820(CAO)		
<b>Labelling:</b>	8		

**15. REGULATORY INFORMATION****Hazard symbols:** Corrosive.

## SAFETY DATA SHEET

TFR AND POLISH

**Risk phrases:** R34: Causes burns.

**Safety phrases:** S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S36/37/39: Wear suitable protective clothing, gloves and eye / face protection.

S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

S2: Keep out of the reach of children.

**Haz. ingredients (label):** SODIUM HYDROXIDE

**Seveso II guideline:** No

**Water hazard class:** 1 Classification by VwVwS

**Air emission directive:** Amount m%: 0

**Note:** The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

### 16. OTHER INFORMATION

**Other information:** This safety data sheet is prepared in accordance with Regulation (EC) No 1907/2006.

**Risk phrases used in s.3:** R36: Irritating to eyes.

R22: Harmful if swallowed.

R41: Risk of serious damage to eyes.

R34: Causes burns.

R35: Causes severe burns.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

